

6254-0B Foot Bellow



Technology Ltd

- Aluminium construction for harsh environments
- With strong conduit tubing
- Temperature range: -10°C to +40°C





Maximum depression time 30 seconds, for applications requiring a greater period please contact sales to discuss further.



Reference Dimensions mm

6254-0B



Specifications

Standards/approvals	N/A	Electrical rating	N/A
Air connection	Compete with 2 m tube (black) with 3mm I/D	Contact configuration	N/A
Alternative air connection	3mm I/D & 6mm O/D, which are available in different length	Operating temperature range	-10° C to +40° C
Electrical rating	N/A	Body material	die-cast aluminium, powder coat black
Pressure range	Works with 6871, 6872, 6773, 6753, 6891, 6893, 6861, 6862, 6863, 6864, 6869 - dependent on tube length	Weight	0.475 kg

Accessories

Part Number	Description
6202-0001	Single Black RAL 9005 guard
6202-0002	Single Grey RAL 7035 guard
6202-0003	Twin Grey RAL 7035 guard



PITCH TECHNOLOGIES

Votre contact HERGA en France

☎ 01 34 85 54 68

🌐 <https://pitch-technologies.fr>
 📧 info@pitch-technologies.fr



Herga Technology Ltd - Northern Way - Bury St. Edmunds - Suffolk - IP32 6NN - UK
 sales@herga.com • www.herga.com • +44 (0)1284 701422

Subject to change without notice