



- ▶ **Low profile, rear hinged switch designed for improved user comfort**
- ▶ **Grey cover with Herga logo fitted on a grey base**
- ▶ **Fitted to a grey moulded 3 pedal base**
- ▶ **Momentary action with normally open contacts**

The 6226-0026 is a 3 pedal footswitch supplied with all grey pedals and base. With N/O contacts, the switch is supplied with 2 metre cable with free wire ends. It has IPX8 rating and is designed for operation at 24 V AC/DC.

Specifications	
Standards/approvals	Footswitch: UL file reference E353500 ANSI/AAI ES60601-1, A1:2012, C1:2009/(R) 2012 and A2:2010 (R) 2012 CSA CAN/CSA-C22.2 No 60601-1-14 IEC 60601-1 Ed 3.1 (2012) EN 60601-1:2006 & A1:2013 & A12:2014 BS EN 62368-1:2014 & A11:2017
Degree of protection	EN 60529 IPX8
Connection method	2 metres of 4-core cable
Max. electrical rating	1.75A, 24VAC/DC
Contact configuration	Normally Open contacts
Action	Momentary
Operating temperature range	-20°C to +60°C
Body material	Thermoplastic
Weight	550 grams (including cable)
Additional information	Customized versions available (logos, cordsets, colours, guards)



### Dimensions

